

A Rock-Solid Warranty for a Rock-Solid Pump


10 yr

Extended 10-Year Limited Pump Warranty Available for Orenco Sewers

Designing a new wastewater collection system?
Considering a pressure sewer, but concerned
about operational costs?

Orenco's lightweight, durable effluent pumps are
easy to maintain, reliable, and field-serviceable.
And for \$25, we're offering an extended warranty
on select PF-series pumps when used in Orenco
Sewers. **That means every one of these pumps
you install can be covered for 10 years.**

See the other side of this flyer for the technical
details that make our pumps the best in the
business. Then, **contact our Municipal Systems
team** today to learn more about Orenco pumps,
Orenco Sewers™, or the extended 10-year limited
warranty. You can call (800) 348-9843 or
+1-541-459-4449, or reach them via email
at info@orenco.com.



Orenco®
Orenco Systems®, Incorporated

PF Series 60-Hz, 4-inch (100-mm) Submersible Effluent Pumps

Applications

Our 4-inch (100-mm) Submersible Effluent Pumps are designed to transport screened effluent (with low TSS counts) from septic tanks or separate dosing tanks. All our pumps are constructed of lightweight, corrosion-resistant stainless steel and engineered plastics; all are field-serviceable and repairable with common tools; 60-Hz PF Series models are CSA certified to the U.S. and Canadian safety standards for effluent pumps, meeting UL requirements.

Orenco's Effluent Pumps are used in a variety of applications, including pressurized drainfields, packed bed filters, mounds, aerobic units, effluent irrigation, effluent sewers, wetlands, lagoons, and more. These pumps are designed to be used with a Biotube® pump vault or after a secondary treatment system.



Features/Specifications

To specify this pump for your installation, require the following:


- Minimum 24-hour run-dry capability with no deterioration in pump life or performance*
- Patented 1/8-inch (3-mm) bypass orifice to ensure flow recirculation for motor cooling and to prevent air bind
- Liquid end repair kits available for better long-term cost of ownership
- TRI-SEAL™ floating impeller design on 10, 15, 20, and 30 gpm (0.6, 1.0, 1.3, and 1.9 L/sec) models; floating stack design on 50 and 75 gpm (3.2 and 4.7 L/sec) models
- Franklin Electric Super Stainless motor, rated for continuous use and frequent cycling
- Type SOOW 600-V motor cable

* Not applicable for 5-hp (3.73 kW) models

Standard Models

See specifications chart, pages 2-3, for a list of standard pumps. For a complete list of available pumps, call Orenco.

Product Code Diagram



Pump, PF Series

* 1/2-hp (0.37kW) only

[†] Available for 10 gpm (0.6 L/sec), 1/2 hp (0.37 kW) only

[‡] Note: 20-ft cords are available only for single-phase pumps through 1 1/2 hp



C US
 LR80980
 LR2053896



Powered by
Franklin Electric